

# Mono-Tape<sup>®</sup> (One Wire) Heavy Insulated Laboratory and Industrial Heating Tape



- HTS/Amptek<sup>®</sup> Heavy Mono-Tape<sup>®</sup> Features:**
- For use on Conductive (Metal) Surfaces.
  - 2 ft. Hi Temperature Leads on **Each** End.
  - 2 Heavy Braided Cover with Ties on Each End.
  - 2 Piece, "Split" Plug Supplied on Each End On Most 120V Tapes.

Cut-Away Configuration	Max Temp	Size		Watts	120V Plug	Cat. No. (120V)	Cat. No. (240V)	USD
		US	CM					
<b>Mono-Tape<sup>®</sup>, Amox High Temp. (1400F 760C) Hvy. Insul. Heating Tape, 13 WSI</b>								
		.5" X 2'	1.3 X 060	156	Yes	AWH-051-020	AWH-052-020	\$ 39.00
		.5" X 4'	1.3 X 120	312	Yes	AWH-051-040	AWH-052-040	\$ 46.00
		.5" X 6'	1.3 X 180	468	Yes	AWH-051-060	AWH-052-060	\$ 57.00
		.5" X 8'	1.3 X 240	624	Yes	AWH-051-080	AWH-052-080	\$ 68.00
		.5" X 10'	1.3 X 300	780	No		AWH-052-100	\$ 82.00
		.5" X 12'	1.3 X 360	936	No		AWH-052-120	\$ 99.00
		1" X 2'	2.5 X 060	312	Yes	AWH-101-020	AWH-102-020	\$ 46.00
		1" X 4'	2.5 X 120	624	Yes	AWH-101-040	AWH-102-040	\$ 62.00
		1" X 6'	2.5 X 180	936	No		AWH-102-060	\$ 79.00
		1" X 8'	2.5 X 240	1248	No		AWH-102-080	\$ 94.00

**HIGH WATT DENSITY**

Cut-Away Configuration	Max Temp	Size		Watts	120V Plug	Cat. No. (120V)	Cat. No. (240V)	USD
		US	CM					
<b>Mono-Tape<sup>®</sup>, Fiberglass, Medium Temp. (900F 482C) Hvy. Insul. Heating Tape, 8.66 WSI</b>								
		.5" X 2'	1.3 X 060	104	Yes	AIH-051-020	AIH-052-020	\$ 33.00
		.5" X 4'	1.3 X 120	208	Yes	AIH-051-040	AIH-052-040	\$ 41.00
		.5" X 6'	1.3 X 180	312	Yes	AIH-051-060	AIH-052-060	\$ 51.00
		.5" X 8'	1.3 X 240	416	Yes	AIH-051-080	AIH-052-080	\$ 61.00
		.5" X 10'	1.3 X 300	520	Yes	AIH-051-100	AIH-052-100	\$ 74.00
		1" X 2'	2.5 X 060	208	Yes	AIH-101-020	AIH-102-020	\$ 41.00
		1" X 4'	2.5 X 120	416	Yes	AIH-101-040	AIH-102-040	\$ 57.00
		1" X 6'	2.5 X 180	624	No	AIH-101-060	AIH-102-060	\$ 70.00
		1" X 8'	2.5 X 240	832	No	AIH-101-080	AIH-102-080	\$ 83.00
		1" X 10'	2.5 X 300	1040	No		AIH-102-100	\$ 95.00

**MEDIUM WATT DENSITY**

# Mono-Tape<sup>®</sup> (One Wire) Standard Insulated




- HTS/Amptek<sup>®</sup> Standard Mono-Tape<sup>®</sup> Features:**
- Use on Non-Conductive Surfaces Such as Glass or Ceramic.
  - 2 ft. Hi Temperature Leads and Ties on **Each** End.
  - 2 Piece, "Split" Plug Supplied on Each End On Most 120V Tapes.

Cut-Away Configuration	Max Temp	Size		Watts	120V Plug	Cat. No. (120V)	Cat. No. (240V)	USD
		US	CM					
<b>Mono-Tape<sup>®</sup>, Amox High Temp. (1400F 760C) Std. Insul. Heating Tape, 13 WSI</b>								
		.5" X 2'	1.3 X 060	156	Yes	AWO-051-020	AWO-052-020	\$ 29.00
		.5" X 4'	1.3 X 120	312	Yes	AWO-051-040	AWO-052-040	\$ 34.00
		.5" X 6'	1.3 X 180	468	Yes	AWO-051-060	AWO-052-060	\$ 45.00
		.5" X 8'	1.3 X 240	624	Yes	AWO-051-080	AWO-052-080	\$ 51.00
		.5" X 10'	1.3 X 300	780	No		AWO-052-100	\$ 59.00
		.5" X 12'	1.3 X 360	936	No		AWO-052-120	\$ 72.00
		1" X 2'	1.3 X 480	312	Yes	AWO-101-020	AWO-102-020	\$ 34.00
		1" X 4'	2.5 X 060	634	Yes	AWO-101-040	AWO-102-040	\$ 45.00
		1" X 6'	2.5 X 120	936	No		AWO-102-060	\$ 53.00
		1" X 8'	2.5 X 180	1248	No		AWO-102-080	\$ 71.00

**HIGH WATT DENSITY**

Cut-Away Configuration	Max Temp	Size		Watts	120V Plug	Cat. No. (120V)	Cat. No. (240V)	USD
		US	CM					
<b>Mono-Tape<sup>®</sup>, Fiber Glass, Medium Temp. (900F 482C) Std. Insul. Heating Tape, 8.66 WSI</b>								
		.5" X 2'	1.3 X 060	104	Yes	AIO-051-020	AIO-052-020	\$ 28.00
		.5" X 4'	1.3 X 120	208	Yes	AIO-051-040	AIO-052-040	\$ 31.00
		.5" X 6'	1.3 X 180	208	Yes	AIO-051-060	AIO-052-060	\$ 40.00
		.5" X 8'	1.3 X 240	416	Yes	AIO-051-080	AIO-052-080	\$ 45.00
		.5" X 10'	1.3 X 300	520	Yes	AIO-051-100	AIO-052-100	\$ 52.00
		1" X 2'	2.5 X 060	208	Yes	AIO-101-020	AIO-102-020	\$ 31.00
		1" X 4'	2.5 X 120	416	Yes	AIO-101-040	AIO-102-040	\$ 41.00
		1" X 6'	2.5 X 180	624	No	AIO-101-060	AIO-102-060	\$ 45.00
		1" X 8'	2.5 X 240	832	No	AIO-101-080	AIO-102-080	\$ 64.00
		1" X 10'	2.5 X 300	1020	No		AIO-102-100	\$ 77.00

**MEDIUM WATT DENSITY**



**Two piece molded plug:** Split plug is standard on 120V Mono-Tapes<sup>®</sup>. To purchase a Mono-Tape<sup>®</sup> without the Split Plug, deduct \$2.00.

**Longer lead wires:** Standard lead wire length for all Mono-Tapes<sup>®</sup> is 24". For longer lengths contact HTS/Amptek<sup>®</sup>

**Special Length, Width, Watts or Volts:** Mono-Tapes<sup>®</sup> may be fabricated to operate on all common voltages, from 12 to 480, and with watt densities from .1 to 13 WSI. Contact HTS/Amptek<sup>®</sup> for free, knowledgeable design assistance.

**HTS/Amptek Company**  
4747 South Main St.  
Stafford, TX 77477  
info@heatingtapes.com