

Wide Heavy Insulated, High Temperature Laboratory and Industrial Heating Tape




HTS/Amptek® Wide

Heavy Features:

- For use on Conductive (Metal) Surfaces.
- 2 ft. Hi Temperature Leads on One End.
- 2 Heavy Braided Cover with Ties on Each End.
- 1 Molded Plug Supplied on most 120V Tapes.

Cut-Away Configuration	Max Temp	Size		Watts	120V Plug	Cat. No. (120V)	Cat. No. (240V)	USD
		US	CM					
AMOX, High Temp. (1400F 760C) Heavy Insulated Heating Tape, 13.0 WSI (element)								
		1.25" X 2'	3.1 X 060	312	Yes	AWH-171-020	AWH-172-020	\$ 89.00
		1.25" X 4'	3.1 X 120	624	Yes	AWH-171-040	AWH-172-040	\$ 121.00
		1.25" X 6'	3.1 X 180	936	Yes	AWH-171-060	AWH-172-060	\$ 167.00
		1.25" X 8'	3.1 X 240	1248	Yes	AWH-171-080	AWH-172-080	\$ 219.00
		1.25" X 10'	3.1 X 300	1560	No		AWH-172-100	\$ 235.00
		2.0" X 2'	5.0 X 060	468	Yes	AWH-251-020	AWH-252-020	\$ 106.00
		2.0" X 4'	5.0 X 120	936	Yes	AWH-251-040	AWH-252-040	\$ 156.00
		2.0" X 6'	5.0 X 180	1404	No	AWH-251-060	AWH-252-060	\$ 210.00
		2.0" X 8'	5.0 X 240	1872	No	AWH-251-080	AWH-252-080	\$ 265.00
		2.0" X 10'	5.0 X 300	2340	No		AWH-252-100	\$ 279.00
		2.5" X 2'	6.2 X 060	624	Yes	AWH-321-020	AWH-322-020	\$ 123.00
		2.5" X 4'	6.2 X 120	1248	No	AWH-321-040	AWH-322-040	\$ 178.00
		2.5" X 6'	6.2 X 180	1872	No	AWH-321-060	AWH-322-060	\$ 243.00
		2.5" X 8'	6.2 X 240	2496	No	AWH-321-080	AWH-322-080	\$ 340.00
		2.5" X 10'	6.2 X 300	3120	No		AWH-322-100	\$ 395.00
	HIGH WATT DENSITY							

Wide Heavy Insulated, Medium Temperature Laboratory and Industrial Heating Tape



Single piece molded plug: Offered as an option on 120V Duo-Tapes®. For the plug option, add the part number suffix **-MP**, Add **\$3.00**

Cut-Away Configuration	Max Temp	Size		Watts	120V Plug	Cat. No. (120V)	Cat. No. (240V)	USD
		US	CM					
Fiber Glass, Medium Temp. (900F 482C) Heavy Insulated Heating Tape, 8.66 WSI (element)								
		1.25" X 2'	3.1 X 060	208	Yes	AIH-171-020	AIH-172-020	\$ 73.00
		1.25" X 4'	3.1 X 120	416	Yes	AIH-171-040	AIH-172-040	\$ 108.00
		1.25" X 6'	3.1 X 180	614	Yes	AIH-171-060	AIH-172-060	\$ 145.00
		1.25" X 8'	3.1 X 240	832	Yes	AIH-171-080	AIH-172-080	\$ 171.00
		1.25" X 10'	3.1 X 300	1040	No		AIH-172-100	\$ 197.00
		2.0" X 2'	5.0 X 060	312	Yes	AIH-251-020	AIH-252-020	\$ 85.00
		2.0" X 4'	5.0 X 120	624	Yes	AIH-251-040	AIH-252-040	\$ 108.00
		2.0" X 6'	5.0 X 180	936	Yes	AIH-251-060	AIH-252-060	\$ 119.00
		2.0" X 8'	5.0 X 240	1248	No	AIH-251-080	AIH-252-080	\$ 177.00
		2.0" X 10'	5.0 X 300	1560	No		AIH-252-100	\$ 238.00
		2.5" X 2'	6.2 X 060	416	Yes	AIH-321-020	AIH-322-020	\$ 95.00
		2.5" X 4'	6.2 X 120	832	Yes	AIH-321-040	AIH-322-040	\$ 138.00
		2.5" X 6'	6.2 X 180	1248	No	AIH-321-060	AIH-322-060	\$ 204.00
		2.5" X 8'	6.2 X 240	1664	No	AIH-321-080	AIH-322-080	\$ 282.00
		2.5" X 10'	6.2 X 300	2080	No		AIH-322-100	\$ 310.00
	MEDIUM WATT DENSITY							

Longer lead wires: Standard lead wire length for all Wide Heavy Tapes is 24". For longer lengths contact HTS/Amptek®

Special Length, Width, Watts or Volts: Wide Heavy Tapes may be fabricated to operate on all common voltages, from 12 to 480, and with watt densities from .1 to 13 WSI. Contact HTS/Amptek® for free, knowledgeable design assistance.

HTS/Amptek Company
4747 South Main St.
Stafford, TX 77477
info@heatingtapes.com