


Duo-Tape[®] (Two Wire) Silicone Extruded Laboratory and Industrial Heating Tapes



HTS/Amptek[®] ASR Duo-Tape[®] Features:

- For use on Conductive (Metal) Surfaces.
- Silicone Rubber Extruded construction.
- For use in Moisture Areas.
- 2 ft. Silicone Rubber Leads on One End
- Optional Plug, available on 120V ASR Tapes.



| Cut-Away Configuration | Max Temp | Size | | Watts | 120V Plug | Cat. No. (120V) | Cat. No. (240V) | USD |
|--|-----------|-----------|------------|--------------|--------------|-----------------|-----------------|-----------|
| | | US | CM | | | | | |
| ASR Duo-Tape[®], Silicone Rubber. (400F 204C) Extruded Heating Tape, Low Watt Density 4.33 WSI | | | | | | | | |
| | | .5" X 2' | 1.3 X 060 | 52 | Option | ASR-051-020D | | \$ 59.00 |
| | | .5" X 4' | 1.3 X 120 | 104 | Option | ASR-051-040D | ASR-052-040D | \$ 70.00 |
| | | .5" X 6' | 1.3 X 180 | 156 | Option | ASR-051-060D | ASR-052-060D | \$ 75.00 |
| | | .5" X 8' | 1.3 X 240 | 208 | Option | ASR-051-080D | ASR-052-080D | \$ 92.00 |
| | | .5" X 10' | 1.3 X 300 | 260 | Option | ASR-051-100D | ASR-052-100D | \$ 97.00 |
| | | .5" X 12' | 1.3 X 360 | 312 | Option | ASR-051-120D | ASR-052-120D | \$ 125.00 |
| | | .5" X 14' | 1.3 X 420 | 364 | Option | ASR-051-140D | ASR-052-140D | \$ 147.00 |
| | | .5" X 16' | 1.3 X 480 | 416 | Option | ASR-051-160D | ASR-052-160D | \$ 168.00 |
| | | .5" X 18' | 1.3 X 540 | 468 | Option | ASR-051-180D | ASR-052-180D | \$ 189.00 |
| | | .5" X 20' | 1.3 X 600 | 520 | Option | ASR-051-200D | ASR-052-200D | \$ 211.00 |
| | | .5" X 24' | 1.3 X 720 | 624 | Option | ASR-051-240D | ASR-052-240D | \$ 232.00 |
| | | .5" X 32' | 1.3 X 690 | 832 | Option | ASR-051-320D | ASR-052-320D | \$ 310.00 |
| | | .5" X 40' | 1.3 X 1200 | 1040 | Option | ASR-051-400D | ASR-052-400D | \$ 387.00 |
| | | 1" X 2' | 2.5 X 060 | 104 | Option | ASR-101-020D | ASR-102-020D | \$ 75.00 |
| | | 1" X 4' | 2.5 X 120 | 208 | Option | ASR-101-040D | ASR-102-040D | \$ 103.00 |
| | | 1" X 6' | 2.5 X 180 | 312 | Option | ASR-101-060D | ASR-102-060D | \$ 119.00 |
| | | 1" X 8' | 2.5 X 240 | 416 | Option | ASR-101-080D | ASR-102-080D | \$ 147.00 |
| | | 1" X 10' | 2.5 X 300 | 520 | Option | ASR-101-100D | ASR-102-100D | \$ 157.00 |
| | | 1" X 12' | 2.5 X 360 | 624 | Option | ASR-101-120D | ASR-102-120D | \$ 180.00 |
| | | 1" X 14' | 2.5 X 420 | 728 | Option | ASR-101-140D | ASR-102-140D | \$ 202.00 |
| 1" X 16' | 2.5 X 480 | 832 | Option | ASR-101-160D | ASR-102-160D | \$ 218.00 | | |
| 1" X 18' | 2.5 X 540 | 936 | Option | ASR-101-180D | ASR-102-180D | \$ 241.00 | | |
| 1" X 20' | 2.5 X 600 | 1040 | Option | ASR-101-200D | ASR-102-200D | \$ 257.00 | | |

LOW WATT DENSITY

Single piece molded plug: Offered as an option on 120V ASR Tapes. For the plug, add the part number suffix **-MP**, Add **\$3.00**.

Special Length, Width, Watts or Volts: Duo-Tapes[®] may be fabricated to operate on all common voltages, from 12 to 480, and with watt densities from .1 to 4.3 WSI. Contact HTS/Amptek[®] for knowledgeable design assistance.

Longer lead wires: Standard lead wire length for all ASR Tapes is 24". For longer lengths contact HTS/Amptek[®]

HTS/Amptek Company
4747 South Main St.
Stafford, TX 77477
info@heatingtapes.com